

Vesta



- 450VA/650VA/850VA/1KVA/1.5KVA/2KVA line interactive UPS
- Built-in super smart charger, shorten 50% of charging time
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- Optional USB/RS-232 communication port and RJ-11/RJ-45 protection
- Offering LED and LCD panels for selections

Vesta 450VA/650VA/850VA/1KVA/1.5KVA/2KVA Line Interactive UPS Selection Guide

MODEL	Vesta 450	Vesta 650	Vesta 850	Vesta 1K	Vesta 1.5K	Vesta 2K
CAPACITY	450 VA / 240 W	650 VA / 360 W	850 VA / 480 W	1000 VA / 600 W	1500 VA / 900 W	2000 VA / 1200 W
INPUT						
Voltage	110/120 VAC or 220/230/240 VAC					
Voltage Range	81-145 VAC / 162-290 VAC					
Frequency Range	60/50 Hz (auto sensing)					
OUTPUT						
AC Voltage Regulation (Batt. Mode)	±10%					
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz					
Transfer Time	Typical 2-6 ms, 10ms max.					
Waveform (Batt. Mode)	Simulated Sine Wave					
BATTERY						
Battery Type & Number	12 V/4.5 Ah x 1	12 V/7 Ah x 1	12 V/9 Ah x 1	12 V/7 Ah x 2	12 V/9 Ah x 2	12 V/9 Ah x 2
Typical Recharge Time	4-6 hours recover to 90% capacity					
PROTECTION						
Full Protection	Overload, discharge, and overcharge protection					
INDICATORS						
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Low Battery					
LED Display	AC Mode	Green lighting			Green lighting	The right green LED lighting & the 2nd to 5th green LEDs gradually lighting indicating load level
	Battery Mode	Green flashing			Yellow flashing	The right green LED flashing & the 2nd to 5th green gradually lighting indicating battery capacity
	Fault	N/A			Red lighting	
ALARM						
Battery Mode	Sounding every 10 seconds					
Low Battery	Sounding every second					
Overload	Sounding every 0.5 second					
Battery Replacement Alarm	Sounding every 2 seconds					
Fault	Continuously sounding					
PHYSICAL						
Dimension, D x W x H (mm)	287 x 100 x 142			350 x 146 x 160	397 x 146 x 205	
Net Weight (kgs)	3.55	4.25	4.9	8.0	11.1	11.5
ENVIRONMENT						
Humidity	0-90 % RH @ 0- 40°C (non-condensing)					
Noise Level	Less than 40dB					
MANAGEMENT						
Optional USB/RS-232 Port	Supports Windows* 2000/2003/XP/Vista/2008, Windows* 7, Linux, Unix, and MAC					

* Product specifications are subject to change without further notice